



MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

Description

The MPC-3120R series Photocoupler is ideally suited for driving power IGBTs and MOSFETs used in motor control inverter applications and inverters in power supply system. It contains an AlGaAs LED optically coupled to an integrated circuit with a power output stage. The 3A peak output current is capable of directly driving most IGBTs with ratings up to 1200 V/100 A. For IGBTs with higher ratings, the MPC-3120R series can be used to drive a discrete power stage which drives the IGBT gate. The Photocoupler operational parameters are guaranteed over the temperature range from -40°C ~ $+110^{\circ}\text{C}$.


Features

- ± 3 A maximum peak output current
- Rail-to-rail output voltage
- Propagation delay time : $T_{PHL} = 300$ ns (max) , $T_{PLH} = 300$ ns (max)
- Under Voltage Lock-Out protection (U_{VLO}) with hysteresis
- 35 kV/us minimum Common Mode Rejection (CMR) at $V_{CM} = 1500$ V
- $I_{CC} = 3$ mA maximum supply current
- Wide operating range: 15 to 30 Volts (V_{CC})
- Guaranteed performance over temperature - 40°C ~ $+110^{\circ}\text{C}$.

Applications

- Plasma Display Panel
- IGBT/MOSFET gate drive
- Industrial Inverter
- Induction heating
- Uninterruptible power supply (UPS)


SCHEMATIC



PIN DEFINITION

1. NC	8. V_{CC}
2. Anode	7. V_O
3. Cathode	6. V_O
4. NC	5. GND

PACKAGE OUTLINE





MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	Note
Storage Temperature	T _{stg}	-40	+125	°C	-
Operating Temperature	T _{opr}	-40	+110	°C	-
Output IC Junction Temperature	T _J		125	°C	-
Total Output Supply Voltage	(V _{CC} - V _{EE})	0	35	V	-
Average Forward Input Current	I _F		20	mA	-
Reverse Input Voltage	V _R		5	V	-
Peak Transient Input Current	I _F (TRAN)		1.0	A	1
“High” Peak Output Current	I _{OH} (PEAK)		3	A	2
“Low” Peak Output Current	I _{OL} (PEAK)		3	A	2
Output Voltage	V _O (PEAK)		35	V	-
Power Dissipation	P _I		45	mW	-
Output Power Dissipation	P _O		250	mW	-
Total Power Dissipation	P _T		295	mW	-
Lead Solder Temperature (10s)	T _{sol}		260	°C	-

Note: Ambient temperature = 25°C, unless otherwise specified. Stresses exceeding the absolute maximum ratings can cause permanent damage to the device. Exposure to absolute maximum ratings for long periods of time can adversely affect reliability.

Note 1: Pulse width (P_w) ≤ 1 μs, 300 pps

Note 2: Exponential waveform. Pulse width ≤ 0.3 μs, f ≤ 15 kHz

TRUTH TABLE

LED	V _{DD} -V _{SS} "Positive Going" (Turn-on)	V _{DD} -V _{SS} "Negative Going" (Turn-off)	V _O
Off	0V to 30V	0V to 30V	Low
On	0V to 11V	0V to 9.5V	Low
On	11V to 13.5V	9.5V to 12V	Transition
On	13.5V to 30V	12V to 30V	High

Note: A ceramic capacitor (0.1 μF) should be connected between pin 8 and pin 5 to stabilize the operation of a high gain linear amplifier. Otherwise, this Photocoupler may not switch properly. The bypass capacitor should be placed within 1 cm of each pin.



MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

ELECTRICAL OPTICAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION	NOTE
INPUT CHARACTERISTICS							
Input Forward Voltage	V _F	1.2	1.37	1.8	V	I _F = 10mA	-
Input Reverse Voltage	B _V R	5	-	-	V	I _R = 10μA	-
Input Threshold Current (Low to High)	I _F L _H	-	1.5	5	mA	V _{CC} = 30 V, V _O > 5V	-
Input Threshold Voltage (High to Low)	V _F H _L	0.8	-	-	V	V _{CC} = 30 V, V _O < 5V	-
Input Capacitance	C _{IN}	-	33	-	pF	f = 1 MHz, V _F = 0 V	-
OUTPUT CHARACTERISTICS							
High Level Supply Current	I _{CC} H	-	1.6	3.0	mA	I _F = 10 mA, V _{CC} = 30V, V _O = Open	-
Low Level Supply Current	I _{CC} L	-	2.0	3.0	mA	I _F = 0 mA, V _{CC} = 30V, V _O = Open	-
High level output current	I _{OH}	-	-	-1.0	A	V _O = (V _{CC} - 1.5 V)	1
		-	-	-3.0		V _O = (V _{CC} - 4 V)	2
Low level output current	I _{OL}	1.0	-	-	A	V _O = (V _{EE} + 1.5 V)	1
		3.0	-	-		V _O = (V _{EE} + 4 V)	2
High level output voltage	V _{OH}	V _{CC} - 0.3	V _{CC} - 0.15	-	V	I _F = 10mA, I _O = -100mA	-
Low level output voltage	V _{OL}	-	V _{EE} + 0.1	V _{EE} + 0.25	V	I _F = 0mA, I _O = 100mA	-
U _{VLO} Threshold	V _{UVLO+}	11.0	12.4	13.5	V	V _O > 5V, I _F = 10 mA	-
	V _{UVLO-}	9.5	11.1	12.0	V	V _O < 5V, I _F = 10 mA	
U _{VLO} Hysteresis	U _{VLOHYS}	-	1.3	-	V	-	-

All Typical values at T_A = 25°C and V_{CC} - V_{EE} = 30 V, unless otherwise specified;

Note 1: Maximum pulse width = 50 μs.

Note 2: Maximum pulse width = 10 μs.



MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

SWITCHING SPECIFICATION

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION	NOTE
Propagation Delay Time to High Output Level	t_{PLH}	50	135	300	ns	$R_g = 10\Omega$, $C_g = 25nF$, $f = 10\text{ kHz}$, Duty Cycle = 50% $I_F = 7\text{ to }16\text{ mA}$, $V_{CC} = 10\text{ to }30\text{ V}$ $V_{EE} = \text{ground}$	
Propagation Delay Time to Low Output Level	t_{PHL}	50	140	300	ns		
Pulse Width Distortion	P_{WD}		5	100	ns		
Propagation delay difference between any two parts or channels	P_{DD}	-100		100	ns		1
Output Rise Time (10 to 90%)	t_r		35		ns		
Output Fall Time (90 to 10%)	t_f		35		ns		
Common mode transient immunity at high level output	$ CM_H $	35			KV/us	$T_A = 25^\circ\text{C}$, $I_F = 10\text{ to }16\text{ mA}$, $V_{CM} = 1500\text{ V}$, $V_{CC} = 30\text{ V}$	2
Common mode transient immunity at low level output	$ CM_L $	35			KV/us	$T_A = 25^\circ\text{C}$, $V_F = 0\text{ V}$, $V_{CM} = 1500\text{ V}$, $V_{CC} = 30\text{ V}$	3

All Typical values at $T_A = 25^\circ\text{C}$ and $V_{CC} - V_{EE} = 30\text{ V}$, unless otherwise specified;

Note 1: The difference between t_{PHL} and t_{PLH} between any two parts under same test conditions.

Note 2: CM_H is the maximum rate of rise of the common mode voltage that can be sustained with the output voltage in the logic high state ($V_O > 15\text{ V}$).

Note 3: CM_L is the maximum rate of fall of the common mode voltage that can be sustained with the output voltage in the logic low state ($V_O < 1\text{ V}$).



MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

TYPICAL PERFORMANCE CURVES & TEST CIRCUITS

Fig.1 High output rail voltage vs. Temperature




Fig.2 V_{OH} vs. Temperature




Fig.3 V_{OL} vs. Temperature




Fig.4 I_{CC} vs. Temperature




Fig.5 I_{CC} vs. V_{CC}





Fig. 6 I_{FLH} Hysteresis





MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

Fig.7 I_{FLH} vs. Temperature




Fig.8 Propagation Delays vs. V_{CC}




Fig.9 Propagation Delays vs. I_F




Fig.10 Propagation Delays vs. Temperature




Fig.11 Propagation Delay vs R_g




Fig. 12 Propagation Delay vs. C_g




Fig.13 Input Current vs. Forward Voltage




Fig.14 I_{OH} Test Circuit




Fig.15 I_{OL} Test Circuit




Fig.16 t_{PHL} , t_{PLH} , t_r and t_f Test Circuit and Waveforms





Fig.17 CMR Test Circuit with Split Resistors Network and Waveforms






MPC-3120R Series


DIP8, DC Input, 3.0A Gate Driver Optocoupler

PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Standard DIP – Through Hole (DIP Type)



Gullwing (400mil) Lead Forming – Through Hole (M Type)



Rev: 2.0


Release Date: 2023/07/26




MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

Surface Mount Lead Forming (S Type)



Surface Mount (Low Profile) Lead Forming (SL Type)



Rev: 2.0


Release Date: 2023/07/26



MPC-3120R Series


DIP8, DC Input, 3.0A Gate Driver Optocoupler

Long Creepage Distance For Surface Mount Type (Option SM)




RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming (S/SL Type)



Long Creepage Distance For Surface Mount Type (Option SM)






MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler


TUBE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Standard DIP



L x W x H = 12.3mm x 10mm x 500mm

Option M



L x W x H = 12.3mm x 10mm x 500mm


BOX SPECIFICATIONS (Tube Type)

Inner Box



L x W x H = 52.5cm x 10.7cm x 4.7cm

Outer Box



L x W x H = 53.5cm x 23.5cm x 25.5cm




MPC-3120R Series


DIP8, DC Input, 3.0A Gate Driver Optocoupler

CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option T1



Option T2






MPC-3120R Series


DIP8, DC Input, 3.0A Gate Driver Optocoupler

REEL SPECIFICATIONS (Dimensions in mm unless otherwise stated)




BOX SPECIFICATIONS (Reel Type)

INNER BOX



L x W x H = 36cm x 36cm x 6.9cm

OUTER BOX



L x W x H = 45cm x 38cm x 38cm




MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

ORDERING AND MARKING INFORMATION

MARKING INFORMATION




M : Company Abbr.
 YY : Year date code
 WW : 2-digit work week
 3120R : Part Number
 T : Factory identification mark
 V : VDE Identification(Option)

ORDERING INFORMATION

MPC-3120RXY(Z)-V

MPC – Company Abbr.
 3120R – Part Number
 X – UVLO Option (None / L)
 Y – Lead Form Option(None/M/S/SL/SM)
 (None-7mm Clearance or M-10mm Clearance or
 S/SL-10mm Clearance or SM-11.8mm Clearance)
 Z – Tape and Reel Option (None /T1/T2)
 V – VDE Option (V or None)

LABEL INFORMATION




PACKING QUANTITY

Option	Quantity	Quantity – Inner box	Quantity – Outer box
None	40 Units/Tube	30 Tubes/Inner box	10 Inner box/Outer box = 12k Units
M	40 Units/Tube	30 Tubes/Inner box	10 Inner box/Outer box = 12k Units
S(T1)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
S(T2)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SL(T1)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SL(T2)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SM(T1)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SM(T2)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units

REFLOW INFORMATION

REFLOW PROFILE



IPC-020d-5-1

Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (T_{smin})	100°C	150°C
Temperature Max. (T_{smax})	150°C	200°C
Time (t_s) from (T_{smin} to T_{smax})	60-120 seconds	60-120 seconds
Ramp-up Rate (t_L to t_P)	3°C/second max.	3°C/second max.
Liquidous Temperature (TL)	183°C	217°C
Time (t_L) Maintained Above (TL)	60 – 150 seconds	60 – 150 seconds
Peak Body Package Temperature	235°C +0°C / -5°C	260°C +0°C / -5°C
Time (t_P) within 5°C of 260°C	20 seconds	30 seconds
Ramp-down Rate (TP to TL)	6°C/second max	6°C/second max
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.




MPC-3120R Series

DIP8, DC Input, 3.0A Gate Driver Optocoupler

TEMPERATURE PROFILE OF SOLDERING

WAVE SOLDERING (JESD22-A111 COMPLIANT)



HAND SOLDERING BY SOLDERING IRON

Soldering Temperature	380+0/-5°C
Soldering Time	3 sec max.

One time soldering is recommended for all soldering method.

Do not solder more than three times for IR reflow soldering.



DISCLAIMER

- WISELITE is continually improving the quality, reliability, function and design. WISELITE reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- WISELITE makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, WISELITE disclaims (a) any and all liability arising out of the application or use of any product, (b) any and all liability, including without limitation special, consequential or incidental damages, and (c) any and all implied warranties, including warranties of fitness for particular.
- The products shown in this publication are designed for the general use in electronic applications such as office automation, equipment, communications devices, audio/visual equipment, electrical application and instrumentation purpose, non-infringement and merchantability.
- This product is not intended to be used for military, aircraft, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Please contact WISELITE sales agent for special application request.
- Immerge unit's body in solder paste is not recommended.
- Parameters provided in datasheets may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated in each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify WISELITE's terms and conditions of purchase, including but not limited to the warranty expressed therein.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.